

# TECHNICKÁ SPECIFIKACE

název série	šířka (L) mm	výška (H) mm	rozteč		hloubka		výkon při tep. spádu			váha kg	objem dm <sup>3</sup>	koeficient n	doporučený výkon el.tyče W
			připojení		od zdi vč. radiátoru (G) mm	od zdi k přívodu (g) mm	55/45	75/65	90/70				
			klasické (hD) mm	středové (h) mm			20°C	20°C	20°C				
PIKO	430	629	400	50	83-103	68-88	132	248	300	3,80	1,60	1,2333	300
		729					150	283	300	4,30	1,80	1,2382	300
		979					195	370	300	5,60	2,40	1,2505	300
		1129					222	419	300	6,40	2,80	1,2454	300
		1329					258	485	600	7,50	3,20	1,2386	600
	530	729	500	50	83-103	68-88	171	322	300	4,80	1,99	1,2424	300
		979					223	421	300	6,30	2,64	1,2435	300
		1129					255	481	600	7,20	3,00	1,2412	600
		1329					298	562	600	8,50	3,60	1,2380	600
		1529					345	649	600	9,70	4,10	1,2340	600
		1679					381	714	600	10,60	4,50	1,2310	900
	630	629	600	50	83-103	68-88	166	315	300	4,80	1,90	1,2507	300
		729					190	360	300	5,40	2,20	1,2466	300
		979					251	471	300	7,00	2,89	1,2366	600
		1129					289	543	600	8,10	3,34	1,2370	600
		1329					339	638	600	9,40	3,90	1,2375	600
		1529					393	738	900	10,80	4,50	1,2363	900
		1679					433	814	900	11,80	5,00	1,2354	900

